



BS EN 14351-1:2006+A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT  
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

**DECLARATION OF PERFORMANCE**

THIS IS TO CERTIFY THAT

**CONNAUGHT WINDOWS LIMITED**

of

496 Wallisdown Road

Bournemouth

Dorset

BH11 8PT

HAVE CONFORMED WITH EN 14351-1:A1:2010 ANNEX ZA

FOR

VERTICAL SIDING & CASEMENT WINDOWS AND DOORS INTENDED TO BE USED  
IN DOMESTIC AND COMMERCIAL LOCATIONS

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION  
CONTROL COMPLYING WITH EN 14351-1:A1:2010 ANNEX ZA

PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORT AND  
PERFORMANCE INDICATION PAPERS FOR ALL COMPONENTS

INCLUDING THE FOLLOWING MANDATORY REQUIREMENTS

LOAD BEARING CAPACITY OF SAFETY DEVICES - Clause 4.8

THERMAL CHARACTERISTICS - Clause 4.12

DANGEROUS SUBSTANCES - Clause 4.6

Signed:

Date:

01-07-13

Position:

MANAGING DIRECTOR



**CONNAUGHT WINDOWS LIMITED**

496 Wallsdown Road

Bournemouth

Dorset

BH11 8PT

13

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT  
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: Metal Windows and Doors with no thermal break

Characteristics	Declared Value
Dangerous Substances	None
Thermal Transmittance	$\leq 4.1W/(m^2K)$
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	npd
Resistance to snow and permanent load	npd
Reaction to fire	npd
External Fire Performance	npd
Water tightness	npd
Impact Resistance	npd
Radiation Properties	npd
Acoustic Performance	npd
Air Permeability	npd

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed:

Date: 01-07-13

Position:

MANAGING DIRECTOR



**CONNAUGHT WINDOWS LIMITED**

496 Wallisdown Road

Bournemouth

Dorset

BH11 8PT

13

EN 14351-1:A1:2010

WINDOWS AND EXTERNAL PEDESTRIAN DOORSETS WITHOUT  
RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

System: PVCu or Timber Windows and Doors

Characteristics	Declared Value
Dangerous Substances	None
Thermal Transmittance	$\leq 3.2W/(m^2K)$
Load Bearing Capacity of Safety Devices	Passed
Resistance to Wind Load	npd
Resistance to snow and permanent load	npd
Reaction to fire	npd
External Fire Performance	npd
Water tightness	npd
Impact Resistance	npd
Radiation Properties	npd
Acoustic Performance	npd
Air Permeability	npd

This declaration relates to a worst case scenario and as such all our products will give an equal to or better (lower) than performance to that quoted

Signed: 

Date: 01-07-13

Position: MANAGING DIRECTOR